

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problems Mailbox.

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau


## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : A61C 3/00	A1	(11) International Publication Number: WO 95/24163 (43) International Publication Date: 14 September 1995 (14.09.95)
(21) International Application Number: PCT/US95/03041 (22) International Filing Date: 10 March 1995 (10.03.95) (30) Priority Data: 08/208,212 10 March 1994 (10.03.94) US 08/401,342 9 March 1995 (09.03.95) US (71) Applicant: IMPLANT INNOVATIONS, INC. [US/US]; 3071 Continental Drive, West Palm Beach, FL 33407 (US). (72) Inventors: BEATY, Keith, D.; 245 Miramar Way, West Palm Beach, FL 33405 (US). HEYLMUN, Thomas, S.; 4387A Willow Pond Road, West Palm Beach, FL 33417 (US). (74) Agent: RUDISILL, Stephen, G.; Arnold, White & Durkee, P.O. Box 4438, Houston, TX 77210 (US).  Lazzara		(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TT, UA, UG, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ, UG).  Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: METHOD AND MEANS FOR AFFIXING A COMPONENT TO A DENTAL IMPLANT

## (57) Abstract

This invention is a tool for affixing a component (10) to a dental implant fixture with a screw (12) passing through the component (10) and threaded into the implant fixture, in which the tool has two parts (28, 40) telescopically inter-fitting one within the other, the outer part (28) being tubular for carrying the component (10) at one end, and the inner part (40) fitted at one end for carrying the screw (12) positioned within the component (10), whereby the component (10) and the screw (12) within it can be carried together to the implant fixture where the outer part (28) is used to hold the component (10) in place, while the inner part (40) is used to drive the screw (12) relative to the implant fixture.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

**METHOD AND MEANS FOR AFFIXING  
A COMPONENT TO A DENTAL IMPLANT**

**Field Of The Invention**

This invention relates to the art of restorative dentistry, and more particularly to that segment of the art which employs artificial roots to restore edentulous patients. This application is a continuation-in-part of pending U.S. patent application  
5 Serial No. 08/208,212, filed on March 10, 1994, which in turn is a continuation-in-part of U.S. patent application Serial No. 08/016,538 filed on February 11, 1993, now issued as U.S. Patent No. 5,322,443.

**Background Of The Invention**

At the present time, owing in part to its predictable success, the endosseous  
10 dental implant fixture in cylindrical form is the artificial root most frequently chosen for restoring dentition to edentulous patients when implant treatment is selected. These and other forms of artificial tooth roots are conveniently designed to receive and retain, sometimes removably, a variety of intermediate components including abutments which prosthodontists use to support artificial dentition on artificial roots.  
15 The intermediate components are necessarily small parts which must be manipulated into sometimes deep posterior locations in the patient's mouth and there assembled on an existing implant fixture or fixtures into rigid and reliable structures which can withstand the forces of mastication. More and more commonly the implant fixtures have internally threaded bores for receiving small screws which are used to attach the  
20 intermediate components to the implant fixtures, and to each other, and they have hexagonal or other non-circular means for anti-rotationally engaging such intermediate components. For biological reasons the implant fixtures and intermediate components are most often made of titanium and its dilute alloys, while the screws are made of the same metals or of gold, for example. Typical diameters  
25 of implant fixtures are from about 3 mm. to about 5 mm. Typical screw diameters are about 2 mm. or less. Typically, intermediate components have diameters in the same range as implant fixtures, and lengths short enough to be encompassed within an artificial tooth, or shorter. The problems of carrying such components to an implant fixture installed in a patient's jawbone and there affixing a component to the  
30 implant with a screw, and rotating the components to engage or mate with anti-

rotational features on the implant fixture, without cross-threading the screw in the threaded bore of the implant fixture, are obvious.

Abutments and other intermediate components are made in a wide variety; some are small transmucosal components as small as one millimeter long, while some are several millimeters long intended to form the core of an artificial tooth; others may extend on an axis different from the longitudinal axis of the implant fixture, for adjusting the alignment of an artificial tooth relative to its neighbors; all must be affixed to the implant fixture. To do this the dental professional must hold the component in place on the implant fixture while inserting a screw through a small hole in the component and turning the screw in the threaded bore of the implant fixture until the screw is tight and the component is firmly affixed to it. This task becomes particularly onerous when the implant fixture is installed in a posterior region in the patient's mouth.

A dental clamp for gripping a cylindrical abutment is shown in U.S. Patent No. 5,120,221 dated June 9, 1992.

#### Summary Of The Invention

In accordance with the present invention, there is provided a tool for use in manually positioning and manipulating a selected article at a prepared implant site in a bone in the mouth of a patient. The tool comprises an article holder having a lower end for engaging the top of the selected article; a fastener passing longitudinally through the article holder for cooperation with the selected article engaged by the lower end of the article holder; a driver mounted for rotation in the article holder and extending downwardly through the article holder for engaging the top of the fastener, so that the fastener can be rotated by rotating the driver, the top of the driver extending above the top of the article holder so that the driver can be turned with the fingers of the person positioning and manipulating the selected article; and a handle attached to the top of the article holder and extending upwardly from the article holder to permit the person positioning and manipulating the selected article to simultaneously position and manipulate the holder and turn the driver with fingers of the same hand.

In one embodiment of the invention, the selected article is an implant carrier, and the fastener is a screw for attaching an implant to the implant carrier. In another

embodiment, the selected article is an implant abutment, and the fastener is a screw for attaching the abutment to an implant.

In the preferred form of the present invention for handling abutments or other intermediate components, the tool employs two telescopically-interfitting parts, the inner one removably attached to the screw head and the other removably attached to a  
5 supragingival end of the intermediate component, for holding the screw and the component in relative positions suitable for installing them on the implant fixture and carrying them to the implant fixture in those positions, and there while holding the component in place on the implant fixture with the outer part using the inner part to  
10 turn the screw into the threaded bore of the implant fixture. Cross-threading of the screw is prevented by virtue of the fact that the component is firmly seated on the implant fixture with the aid of the outer part and the two telescopically interfitting parts align the screw accurately with relation to the threaded bore. The two interfitting parts can be designed to form an assembly including resilient means, such  
15 as a spring, to enable the inner part to press down on the outer part while turning the inner part, so that the entire installation procedure can be completed with two fingers (e.g.: thumb and forefinger) while turning the inner part to install the screw. When the installation procedure is finished both parts can be detached from the screw and the component simply by pulling them away in the supragingival direction. It is not  
20 necessary to tighten the screw to its final torque limit with the carrying and affixing means of the present invention; that task can be performed with a separate torque-limited driver.

The invention lends itself to packaging in a sealed container, which may be a sterile container if desired, so that a component and related screw may be delivered  
25 to a dental professional in a "ready for installation" condition. Thus, the present invention simplifies an onerous task while improving the accuracy with which that task is done, and saves the user valuable time while reducing the risk of infection.

In the preferred form of the invention for use in handling an implant carrier to manually insert a dental implant into a prepared implant site in a bone in the mouth  
30 of a patient, the tool comprises a holder for the implant carrier, the holder having a lower end for engaging the top of the implant carrier so that the implant carrier is retained in the holder; a driver mounted for rotation in the holder and extending

downwardly through the holder for engaging the top of the screw, so that the screw can be rotated by rotating the driver, the top of the driver extending above the top of the holder so that the driver can be turned with the fingers of the person installing the implant; and a handle attached to the top of the holder and extending upwardly from the holder to permit the person installing the implant to simultaneously manipulate the holder and turn the driver with fingers of the same hand. Mating male and female anti-rotation elements are formed on the top of said implant and the bottom of said implant carrier, and the bottom of the holder forms a socket for receiving the top of the implant carrier. The handle is formed as an integral part of said holder, and extends over the top of the driver. The top of the driver forms an enlarged head which extends laterally beyond the handle to facilitate turning of the driver with the same fingers that grip the handle.

#### Brief Description Of The Drawings

The appended drawings illustrate the background of the invention and exemplary embodiments of it. In these drawings:

FIGURES 1 and 2 illustrate, respectively, a transmucosal component and related screw and a dental implant fixture on which they are to be installed;

FIGS. 1A and 1B are end views of FIG. 1;

FIG. 3 illustrates a tubular part for holding the transmucosal component;

FIG. 4 illustrates a part for holding the screw;

FIG. 5 shows the parts of FIGS. 3 and 4 telescopically interfitted and holding the transmucosal component and the screw in the relative positions they will occupy for installation on the implant fixture;

FIG. 5A is a modification of FIG. 5;

FIG. 6 is a side view of another embodiment of the invention;

FIG. 7 is a longitudinal section through FIG. 6 showing a spring used to aid in a two-finger installation;

FIG. 8 is an exploded view of the parts of the embodiment shown in FIGS. 6 and 7;

FIG. 9 is a longitudinal view partly in sections showing the embodiment of FIG. 6 in a sealed container;

FIG. 10 is a longitudinal section through a modified embodiment of the invention for use in handling and manipulating an implant carrier and its attachment screw;

FIG. 11 is an end view taken from the top end of the assembly shown in FIG. 10; and

FIG. 12 is a section taken generally along line 12-12 in FIG. 10.

Detailed Description Of The Preferred Embodiments

FIGS. 1 and 2 show a typical transmucosal component 10 and a typical screw 12 for use to install the transmucosal component on a dental implant fixture 14 which has been installed in jawbone 16. The screw and the transmucosal component are shown in relative positions suitable for installing them on the implant fixture, which has an internally-threaded bore 18 for receiving the screw. As is typical in the art, the implant fixture may have an anti-rotation boss 20 extending supragingivally from it, and the transmucosal component 10 may have a mating socket 22 for interfitting with the boss 20. In practice, the boss and the socket may be reversed. In either case, the transmucosal component must be fitted to the implant fixture with these anti-rotation devices engaged one in the other, prior to turning the screw 12 into the bore 18.

FIG. 3 shows in longitudinal section a tubular holder part 28 for the transmucosal component 10. The internal diameter of this holder part is expanded at its lower end 30 to provide a recess with an internal shoulder 36 for receiving the supragingival end of the transmucosal component. The wall around the recess can be longitudinally slotted if desired to provide a circular array of resilient fingers (see FIG. 6) for releasibly holding the transmucosal component; alternatively the holder part 28 can be made of a resilient plastic material, in which case the wall around the recess can be continuous and the normal resilience of the plastic material will suffice to do the same thing. At its other end the holder has an expanded head 32 gripping it and a second internal shoulder 34 for a purpose to be described.

The second holder part 40 shown in FIG. 4 is cylindrical in shape for telescopically fitting within the tubular holder part 28. This second part has a socket 42 in its lower end 44 for embracing the head 13 of the screw 12. This particular screw has a hexagonally-shaped head, and the socket 42 in the illustrated embodiment

is matingly hexagonal. This is an optional feature adopted to accommodate a particular screw; the invention is not limited to it. For example, the male-female relation of the head 13 and the socket 42 may be reversed. An annular boss 46 is also located near the lower end 44. When, as is illustrated in FIG. 5, the second holder part 40 is telescopically fitted within the tubular holder part 28 the boss 46 will stop against the second shoulder 34.

Referring now to FIG. 5, the two holder parts are shown with the second part 40 telescopically interfitted in the tubular part 28. To do this, the second part with the screw 12 engaged may be inserted through the lower end 30 of the tubular part 28, and thereafter the transmucosal component 10 may be attached to the tubular part. This arrangement provides an assembly of the holder-carrier 28, 40 and the dental components 10, 12 which can be brought as a unit to the dental implant fixture 14 with two fingers (e.g.: thumb and forefinger) of one hand holding the assembly by the expanded head 32. At the implant fixture, the transmucosal component is then manipulated into place on the implant fixture and, while gently holding the transmucosal component against the implant fixture, the second holder part is turned to drive the screw 12 into the threaded bore 18. This assembly can be delivered as a unit to the end user, i.e.: a prosthodontist, periodontist, oral surgeon or other qualified dental professional. It lends itself to encapsulation in a sterile package, if desired.

In FIG. 5A a manipulator 130 is fixed to the upper end of the second (driver) part 40, and holder means 132 having a bight portion 132a and two substantially parallel arms 132b and 132c is attached at the free ends of the arms to substantially diametrically opposite sides of the head 32 of the holder part 28. The bight portion 3132a overlies the manipulator 130, and the manipulator fits between the arms 132b and 132c. In use, the holder means carries the assembled tool with the screw 12 and component 10 to a work site, where the bight portion 132a can be used to press the component to the implant with one finger while the manipulator can be turned with two other fingers of the same hand.

The embodiment of the invention that is illustrated in FIGS. 6, 7 and 8 is unitary tool which includes a means to hold down the tubular part of the invention while turning the screw component with the second part of the invention. This

embodiment is also designed to be compact so that it will minimally obscure the user's view of the task being performed, and will be easy and economical to package and ship. The outer tubular part 50 has spring-fingers 52 separated by longitudinal slots 54 at its lower end 56 for holding the abutment 10. The inner second part 60 is an assembly of two members, a head member 60.2 and a screw-holder member 60.1 having a stem 60.3. The tubular part 50 has a diametrically reduced section 58 between its ends providing a first shoulder 58.1 facing the lower end 56 and a second shoulder 58.2 facing in the opposite direction. The holder member 60.1 has a socket member 60.4 of larger diameter than its stem 60.3 affixed to the lower end of the stem, and forming a shoulder 60.5 where it joins the stem. The socket member has a non-round socket 62 for holding the matingly non-round head 64 of a screw 66 which is equivalent to the screw 12. To assemble this tool the stem 60.3 is passed through the lower end 56 of the tubular part 50 and through the reduced section 58 so that the shoulders 58.1 and 60.5 confront each other, a coil spring 68 is fitted over the stem 60.3 in the upper well 70 of the tubular part, and the head member 60.2 is press-fitted onto the free end of the stem. A turning knob 72 is provided on the free end of the head member.

In use, the screw 66 is fitted into the socket 62 and the component 10 is thereafter fitted into the spring fingers 52. This assembly is then carried to the installed implant fixture and the abutment is put in place on the implant fixture with the outer part 50. The knob 72 may then be grasped between the thumb and forefinger and pressed down toward the implant while the knob is turned to drive the screw into the implant fixture. The spring 68 provides resilient force to hold the component 10 on the implant while the screw is being turned.

The tool of FIGS. 6, 7 and 8 may be made of materials such as stainless steel which can be autoclaved. No lubricant is used in its construction. Alternatively this tool can be made of disposable materials and it can be delivered to the user in a sterile package including the component and screw to be installed on an implant fixture.

FIG. 9 shows the tool of FIG. 6 enclosed in a capsule 80, which may be made of glass or plastic, for example, and is closed with a cap 82 which may be made of rubber or plastic, for example. The outer tubular part 50 is located with an O-ring

84 within the capsule. As is shown, the abutment 10 may be held against the bottom of the capsule, to prevent it from falling away from the spring fingers 52. In use, the cap 82 is removed and the tool is removed from the capsule with the turning knob 72 which is then used to carry the abutment 10 and screw 66 directly to the dentalimplant fixture 14.

A modified embodiment of the invention, for use in handling and manipulating a dental implant carrier, is illustrated in FIGS. 10 - 12. An implant carrier is a device that is used to hold an implant as it is inserted into a patient's mouth and installed into a prepared site in the patient's jawbone. The carrier is also used to turn the implant to thread it into the jawbone.

In FIG. 10, an implant carrier 200 has a hexagonal socket 201 formed in its lower end for receiving a complementary hexagonal head 202 on the top of a dental implant 203. The implant 203 is held securely on the carrier 200 by a screw 204 which extends longitudinally through the hollow interior of the carrier 200 and is threaded into an internally threaded bore in the top of the implant. To prevent the screw 204 from escaping from the carrier 200, the screw 204 must be threaded through a short internally threaded section 205 of the carrier before the screw can be threaded into the implant. Thus the screw is captured within the carrier 200.

To permit the implant 203 to be threaded into the jawbone of the patient by turning the carrier 200, which will still extend well above the gingiva even when the implant is in its desired final position within the jawbone, the carrier has a hexagonal head 206 that can be engaged by a standard wrench or other suitable driver. Turning the carrier 200 causes turning of the implant 203. After the implant has been threaded into the patient's jawbone, the screw 204 is threaded out of the implant to permit the carrier and its captive screw to be removed from the implant and the patient's mouth.

For the purpose of facilitating the handling and placement of the carrier-implant assembly, a holder 210 has a hexagonal socket 211 in its lower end for receiving and frictionally retaining the hexagonal head 206 of the carrier 200. Captured within the holder 210 is a driver 212 having a small hexagonal head 213 on its lower end, for engagement with a complementary hexagonal socket 214 in the top of the carrier screw 204. If desired, the driver may be designed as described in U.S.

Patent No. 5,105,690, which is incorporated herein by reference. The driver 212 can be rotated within the holder 210 for threading the screw 204 in and out of the implant 203, which is particularly useful for removal of the screw from the implant after the implant is in place in the patient's mouth.

5           As in the case of the holder described above in connection with FIG. 5a, the holder 210 has a handle or manipulator 215 extending upwardly from, and diametrically across, the top of the holder. This handle 215 extends across the top of the driver 212, which is equipped with a knurled knob 216 which extends laterally beyond opposite sides of the handle 215 (see FIG. 11). Consequently, both the  
10   handle 215 and the knob 216 can be simultaneously gripped and manipulated with the thumb and forefinger of the person installing the implant in the patient. This is a significant advantage when working within the close confines of a patient's mouth.

          If desired, the holder 210 can also be used as the driving tool for turning the implant carrier 200, and thus the implant itself, to thread the implant into the  
15   patient's jawbone. Here again, the handle 215 on the top of the holder 210 can be used to advantage.

What we claim is:

1. A tool for affixing a component to a support having a receiver member adapted to receive an attaching member for affixing said component, said tool forming an assembly comprising:

5 a first part for holding said component;

a second part for holding said attaching member;

means to fix said parts in a substantially coaxial relation with said second part rotatable within first part, said second part having manipulator means at a first end of said second part; and

10 holder means fixed to said first part and overlying said manipulator means for carrying said assembly and for holding said first part against said support while rotating said second part within said first part with said manipulator means.

2. A tool according to claim 1 in which said first part is hollow and said second part is fitted rotatably within said first part.

15 3. A tool according to claim 1 in which said first part is adapted at a second end to detachably engage one end of said component and said second part is adapted at an end remote from said manipulating means to detachably engage one end of said attaching member.

20 4. A tool according to claim 1 in which the ends of said two parts at an end of said assembly remote from said manipulating means are adapted to detachably engage respectively one end of said component and one end of said attaching member.

5. A tool according to claim 1 including retainer means within said first part to keep said second part within said first part.

25 6. A tool according to claim 1 including compressible resilient means between said second part and said first part for coupling to said first part in the direction of said axis toward said first end thereof, force applied to said second part in the direction of said axis toward said first end thereof.

7. A tool according to claim 6 in which said resilient means is a spring.

30 8. A tool according to claim 7 in which said spring is coiled around said second part.

9. A tool according to claim 8 in which said first part has a shoulder and said spring is fixed between said shoulder and said manipulating means.

10. a tool according to claim 8 in which said spring is coiled around said second part within said first part.

5 11. A tool according to claim 10 in which said first part has an internal shoulder and said spring is fixed between said shoulder and said manipulating means.

12. Carrying and affixing tool means for use to affix a dental component to an artificial root installed in a patient's jawbone which root has an internally-threaded bore opening gingivally, said component having a through-bore for passing a threaded  
10 bolt, said bolt being engageable in said threaded bore for affixing said component to said root, said tool means forming an assembly comprising:

an elongated driver part adapted at a first end for engagement with a head end of said bolt;

a hollow holder part adapted at a first end for engagement with said  
15 component at a supragingival end thereof, said driver part being rotatable within said holder part for holding said bolt within said through-bore when said component and said bolt are engaged with said tool means, so as to enable driving said bolt into said threaded bore with said driver part while holding said component to said root with said holder part, said driver part having manipulator means remote from said first  
20 end and accessible at a second end of said holder part; and

holder means fixed to said holder part and overlying said manipulator means for carrying said assembly and for holding said holder part against said root while rotating said driver part within said holder part with said manipulator means.

13. Tool means according to claim 12 in which said driver part is  
25 elongated on an axis.

14. Tool means according to claim 13 including retainer means to keep said driver part within said holder part.

15. Tool means according to claim 14 in which said retainer means is a section of reduced cross-section within said holder part.

30 16. Tool means according to claim 13 having said manipulator means at the second end of said driver part.

17. Tool means according to claim 16 including compressible resilient means between said driver part and said holder part for coupling to said holder part in the direction of said axis toward said one end thereof, force applied to said driver part in the direction of said axis towards said one end thereof.

5 18. Tool means according to claim 17 in which said resilient means is a spring.

19. Tool means according to claim 18 in which said spring is coiled around said driver part within said holder part.

20. Tool means according to claim 19 in which holder part has an internal shoulder and said spring is fixed between said shoulder and said manipulator means.

21. A method of affixing a dental component to an artificial root installed in a patient's jawbone, which root has an internally-threaded bore, and which component has a through-bore within which to receive a threaded bolt that is engageable in said threaded bore for affixing said component to said root, said method comprising

15 grasping said bolt at its head end with one end of an elongated detachable driver,

with said driver attached inserting said bolt within said component extending through said through-bore, grasping said component at a supragingival end thereof with a hollow holder telescopically surrounding said driver,

20 carrying said component and said bolt within it to said root with said holder and driver telescopically engaged, and placing said component on said root with said bolt in position to be engaged in said threaded bore,

pressing said component to said root with force applied through said holder, turning said driver within said holder to engage said bolt in said threaded bore while holding said component pressed on said root with said holder until said bolt is sufficiently engaged in said threaded bore to affix said component to said root, and thereafter detaching said holder and said driver from said component and said bolt respectively.

30 22. An assembly of a dental component adapted to be affixed to a substructure fixed in a patient's jawbone, said assembly comprising

an attaching member cooperable with said substructure for affixing said component thereto, and

5 tool means comprising a first part for holding said component and a second part for holding said attaching member, said component being removably engaged endwise with said first part and said attaching member being removably engaged endwise with said second part, said tool means including

means to fix said parts in a spatial relation with one part rotatable relative to the other such that if said first part is manipulated to bring said component to said substructure, said second part will be disposed to manipulate said attaching member  
10 to said component to said substructure, said second part having manipulator means accessible at an end of said first part remote from said component, and

holder means fixed to said first part and overlying said manipulator means for carrying said assembly and for holding said first part against said substructure while rotating said second part relative to said first part with said manipulator means.

15 23. An assembly according to claim 22 and a removable enclosure surrounding said assembly.

24. An assembly and an enclosure according to claim 23 in which said enclosure is a sterile package.

20 25. A tool according to claim 1 in which said holder means is a U-shaped member having two substantially parallel arms and a bight portion, the bight portion of which overlies said manipulator means, the free ends of said arms being attached to said first part at points which are substantially diametrically opposite each other.

26. A tool according to claim 25 in which said manipulator means fits between said arms.

25 27. Tool means according to claim 12 in which said holder means is a U-shaped member having two substantially parallel arms and a bight portion, the bight portion of which overlies said manipulator means, the free ends of said arms being attached to said first part at points which are substantially diametrically opposite each other.

30 28. Tool means according to claim 27 in which said manipulator means fits between said arms.

29. An assembly according to claim 22 in which said holder means is a U-shaped member having two substantially parallel arms and a bight portion, the bight portion of which overlies said manipulator means, the free ends of said arms being attached to said first part at points which are substantially diametrically opposite each other.

30. An assembly according to claim 29 in which said manipulator means fits between said arms.

31. A tool for use in manually inserting a dental implant into a prepared implant site in a bone in the mouth of a patient, said tool comprising  
an implant carrier having a lower end for engaging the top of the dental implant so that the implant can be rotated by rotating the carrier,  
a screw passing longitudinally through the implant carrier and threaded into the top of the dental implant for holding the implant on the implant carrier,  
a holder for the implant carrier, said holder having a lower end for engaging the top of the implant carrier so that the implant carrier is retained in the holder,  
a driver mounted for rotation in said holder and extending downwardly through said holder for engaging the top of said screw, so that said screw can be rotated by rotating the driver, the top of said driver extending above the top of said holder so that said driver can be turned with the fingers of the person installing the implant, and  
a handle attached to the top of said holder and extending upwardly from said holder to permit the person installing the implant to simultaneously manipulate said holder and turn said driver with fingers of the same hand.

32. The tool of claim 31 wherein mating male and female anti-rotation elements are formed on the top of said implant and the bottom of said implant carrier.

33. The tool of claim 31 wherein the bottom of said holder forms a socket for receiving the top of said implant carrier.

34. The tool of claim 31 wherein said handle is formed as an integral part of said holder.

35. The tool of claim 31 wherein said handle extends over the top of said driver.

36. The tool of claim 31 wherein the top of said driver forms an enlarged head which extends laterally beyond said handle to facilitate turning of said driver with the same fingers that grip said handle.

5 37 The tool of claim 31 wherein mating male and female anti-rotation elements are formed on the top of said screw and the bottom of said driver.

38. A tool for use in manually positioning and manipulating a selected article at a prepared implant site in a bone in the mouth of a patient, said tool comprising

10 an article holder having a lower end for engaging the top of the selected article,

a fastener passing longitudinally through said article holder for cooperation with the selected article engaged by the lower end of said article holder,

15 a driver mounted for rotation in said article holder and extending downwardly through said article holder for engaging the top of said fastener, so that said fastener can be rotated by rotating the driver, the top of said driver extending above the top of said article holder so that said driver can be turned with the fingers of the person positioning and manipulating the selected article, and

20 a handle attached to the top of said article holder and extending upwardly from said article holder to permit the person positioning and manipulating the selected article to simultaneously position and manipulate said holder and turn said driver with fingers of the same hand.

39. The tool of claim 38 wherein said selected article is an implant carrier, and said fastener is a screw for attaching an implant to said implant carrier.

25 40. The tool of claim 38 wherein said selected article is an implant abutment, and said fastener is a screw for attaching said abutment to an implant.

41. The tool of claim 38 wherein said driver has a knob on its upper end to facilitate turning said driver, and said handle extends across the top of said knob to facilitate manipulation of said article holder with the same fingers used to turn said driver.

1/9




FIG. 1B




FIG. 1




FIG. 1A




FIG. 2

3/9




FIG. 3





FIG. 4



5/9



**FIG. 5A**




FIG. 6




FIG. 7





FIG. 9

FIG. 8




FIG. 10




FIG. 11




FIG. 12

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US95/03041

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :A61C 3/00

US CL :81/451; 433/141, 173

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 81/451; 433/141, 173, 174

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched  
NONEElectronic data base consulted during the international search (name of data base and, where practicable, search terms used)  
NONE

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US, A, 5,064,375, (JORNEUS), 12 November 1991. See entire document.	1-41
A	US, A, 5,145,371, (JORNEUS), 08 September 1993. See entire document.	1-41
A	US, A, 5,062,800, (NIZNICK), 05 November 1991. See entire document.	1-41
A	US, A, 2,276,470, (E. A. DODELIN), 17 March 1942. See entire document.	1-41

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

*A*	document defining the general state of the art which is not considered to be part of particular relevance	*T*	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*E*	earlier document published on or after the international filing date	*X*	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*L*	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (to be specified)	*Y*	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*O*	document referring to an oral disclosure, use, exhibition or other means	*A*	document member of the same patent family
*P*	document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

19 MAY 1995

Date of mailing of the international search report

10 JUL 1995

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

CARY O'CONNOR

Telephone No. (703) 308-2701